

PRODUCT SPECIFICATION**Brite-Line Removable Blackout 100
Pavement Masking Tapes**

Brite-Line Removable Blackout 100 masking tape is an easy to install, highly durable, completely removable means of providing a temporary cover for permanent roadway delineation. Series 100 Blackout Tape is available in a variety of widths, and is intended primarily for construction zones when permanent markings are masked out temporarily but will be used in the future.

Composition

Removable Blackout 100 consists of a layer of anti-skid particles bonded to the specially formulated blend of polymer resins, pigments, fillers, and an integrated reinforcing system. The bottom side of Removable Blackout 100 is coated with a unique pressure sensitive adhesive designed to adhere to properly prepared surfaces; road delineation markings, without the use of heat, solvents, or other extra measures.

Application

Proper surface preparation is essential for satisfactory Removable Blackout 100 results. Essentially, the surface must be clean and dry, with a surface temperature of 50°F, and rising. Removable Blackout 100 cannot be successfully applied over loose or caked dirt, gravel, oily residues, road salt residues, or other foreign substances which will interfere with proper bonding. Manufacturer's application instructions, with more detailed information, are included in each carton.

Skid Resistance

The surface of Removable Blackout 100 provides excellent skid resistance. When tested according to the procedures specified in ASTM-E-303, Removable Blackout 100 exhibits an initial minimum skid resistance value of 45 BPN.

Removal

Removable Blackout 100 temporary tape is designed to allow removal intact or in large pieces. The use of heat, solvents, hydroblasting, or grinding is not needed. It may be necessary to use a sharp edge to start the removal of Removable Blackout 100, then lift one edge of the tape and pull at a 90° angle to the surface. The temperature should be 40°F or higher. At lower temperatures, Removable Blackout 100 may be somewhat more difficult to remove and excess breakage may occur.

Important Notice To Buyer:

All statements, technical information and recommendations contained herein are based on tests believed to be reliable. The accuracy or completeness thereof is not guaranteed, and the following is made in lieu of all warranties, express or implied:

Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use of, or the inability to use the product. Before using, user shall determine the suitability of the product for the intended use, and user assumes all risk and liability whatsoever in connection therewith.

Statements or recommendations not contained herein shall have no force or effect unless in an agreement signed by officers of seller and manufacturer.