

PRODUCT DATA SHEET**Deltaline® BXP****Black Extended Performance Patterned Tape**

Deltaline® BXP is an easy to install, highly durable means of providing a non-reflective contrast or shadow for permanent roadway delineation on concrete or light colored surfaces.

Composition

Deltaline® BXP consists of a layer of anti-skid particles bonded to a conformable matte black patterned surface of specially formulated polymer resins, pigments, fillers and an integrated reinforcing system. It is coated with a pressure sensitive adhesive on the bottom surface for ease of application. Deltaline® BXP is manufactured without the use of heavy metals, lead chromate, pigments, or other similar lead containing chemicals.

Skid Resistance

The surface of Deltaline® BXP provides excellent skid resistance. When tested according to the procedures specified in ASTM-E-303, Deltaline® BXP exhibits an initial minimum skid resistance value of 45 BPN.

Application

All applications using Deltaline® BXP tape can be installed by following the instructions listed on the appropriate Brite-Line® product application instructions.

Important Notice to Buyer

All statements, technical information and recommendations contained herein are based on tests believed to be reliable. The accuracy or completeness thereof is not guaranteed, and the following is made in lieu of all warranties, express or implied:

Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use of, or the inability to use the product. Before using, user shall determine the suitability of the product for the intended use, and user assumes all risk and liability whatsoever in connection therewith.

Statements or recommendations not contained herein shall have no force or effect unless in an agreement signed by officers of seller and manufacturer.